APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No.   PW 0305076
<div align="center">(M#)</div>

Invention: DISK DRIVE WITH COPY FUNCTION

Inventor (s):   MAKI, Yuuko

For correspondence Address

00909

Pillsbury Winthrop LLP

This is a:

☐ Provisional Application

☒ Regular Utility Application

☐ Continuing Application
☐ The contents of the parent are incorporated by reference

☐ PCT National Phase Application

☐ Design Application

☐ Reissue Application

☐ Plant Application

☐ Substitute Specification
Sub. Spec Filed _____
in App. No. _____ / _____

☐ Marked up Specification re
Sub. Spec. filed _____
In App. No _____ / _____

SPECIFICATION

TITLE OF THE INVENTION

DISK DRIVE WITH COPY FUNCTION

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2002-253069, filed August 30, 2002, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to the field of disk drives and, in particular, to a disk drive having the function to copy data which is recorded on a disk medium onto an external device.

2. Description of the Related Art

In general, a disk drive typical of a hard disk drive (HDD) uses a disk medium as a recording medium and allows data to be recorded on the disk medium and the recorded data to be reproduced from the disk medium.

In recent years, the disk drive has been used also as a digital recording device not only in personal computers, etc., for handling computer data, but also in cellular telephones, etc., for handling communication data and in other devices for handling AV (audio-visual) data, etc.

Under such circumstances, a growing demand has

arisen for copying the data which is recorded on a disk medium of one disk drive onto the same kind of an HDD or a different kind of optical disk drive such as a CD-RAM.

In a disk drive such as an HDD, when the data recorded on an internal disk medium is to be copied onto an external disk drive, it has been necessary to control a host system such as a PC. Stated in more detail, it has been necessary to perform a copying operation through an OS of the host system.

As set out above, however, a small-sized disk drive is used not only as an external device of the PC but also as various kinds of digital recording devices and it is desirable to independently realize the copying function irrespective of the host system.

As the prior art technique, a device has been proposed by which a still image can be transferred from a built-in disk drive of a system to an external disk drive (See JPN PAT APPLN KOKAI PUBLICATION NO. 11-259961). In the prior art technique disclosed, the copying operation from the built-in drive to the external drive is achieved under control of the host system. As another prior art technique, a host system has also been proposed under which a disk recorder connected to SCSI bus functions as an initiator and recorded data is transferred to the hard disk device (See JPN PAT APPLN KOKAI PUBLICATION NO. 2000-347990).

Even in this prior art technique, however, a CPU of a host system is used under which the disk recorder functions as an initiator and a copying function is achieved under control of the host system.

BRIEF SUMMARY OF THE INVENTION

In accordance with one embodiment of the present invention, there is provided a disk drive including facilities to copy data read from a disk medium to an external device.

The disk drive comprises a head configured to read recorded data from a disk medium; a read channel configured to reproduce data from the read signal which is output from the head; a command unit configured to instruct a copying operation for allowing the data which is reproduced by the read channel to be transferred to an external device; an interface unit configured to effect a data transfer relative to the external unit; and a control unit configured to, in accordance with the copying operation instructed by the command unit, perform the copying operation while allowing the reproduced data to be transferred to the external device through the interface unit.

Additional embodiments and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the

invention. The embodiments and advantages of the
invention may be realized and obtained by means of the
instrumentalities and combinations particularly
pointed out hereinafter.

5   BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated
in and constitute a part of the specification,
illustrate embodiments of the invention, and together
with the general description given above and the

10   detailed description of the embodiments given below,
serve to explain the principles of the invention.

FIG. 1 is a block circuit showing a structure of
a disk drive relating to an embodiment of the present
invention;

15   FIG. 2 is a block circuit for explaining
a copying operation between disk drives relating to
the present embodiment;

FIG. 3 shows a flowchart for explaining a process
of a copying operation relating to the present

20   embodiment;

FIG. 4 is a flowchart for explaining an operation
of a copying destination drive relating to the present
embodiment;

FIG. 5 is a view showing an external appearance

25   of a disk drive relating to the present embodiment;

FIG. 6 is an external view showing a state of
a connection between a copying source disk and the

copying destination disk in the present embodiment;

FIG. 7A and 7B, each, are a view for explaining a transmit sequence based on the serial ATA Interface Standard in the present embodiment;

5   FIG. 8 is a view for explaining a structure of register groups based on the serial ATA Interface Standard in conjunction with the present embodiment; and

FIG. 9 is a block view relating to a variant of

10   the present embodiment.

DETAILED DESCRIPTION OF THE INVENTION

An embodiment of the present invention will be explained below by referring to the drawing.

(Structure of Disk Drive)

15   FIG. 1 is a block diagram showing a structure of a disk drive 100 relating to the present embodiment. FIG. 2 is a block diagram for explaining a copying operation between the present drive 100 assumed as the structure of a copying source disk drive and a disk

20   drive 200 serving as a copying destination drive.

The present drive 100 is comprised of an HDD including, as shown in FIG. 1, a disk medium 1, a head 2, a disk controller (HDC) 9, a CPU (microprocessor) 10 and a switch 12.

25   The disk medium 1 is rotated by a spindle motor (SPM) 3 to allow data which is written by the head 2 to be recorded thereon.   The head 2 includes a write

head for writing the data to the disk medium 1 and a read head for reading the data from the disk medium 1. The head 2 is mounted on an actuator 4 and moved in a radial direction over the disk medium. The actuator 4 is driven by a voice coil motor (VCM) 5. A motor driver IC 6 includes a VCM driver 60 and SPM driver 61, these drivers driving a VCM 5 and SPM 3 under control of the CPU 10.

The HDC 9 includes a host interface 90 between the present drive 100 and an external device and, under control, mainly effects the transfer of the read/write data (see FIG. 2). The HDC 9 temporarily stores the read/write data in a buffer RAM 11 and adjusts the data transfer speed. Further, the HDC 9 effects data transfer relative to the disk medium 1 through a preamplifier circuit 7 and read/write channel 8.

The preamplifier circuit 7 has a read amplifier for amplifying a read signal read out by the read head of the head 2. Further, the preamplifier circuit 7 has a write amplifier for converting a write signal which is sent from the read/write channel 8 to a current and supplying the current to the write amplifier.

The read/write channel 8 is comprised of a signal processing IC generally separated into a read channel and a write channel. The read channel processes

a read signal which is transferred through the read

head and read amplifier and reproduces data which is

recorded on the disk medium 1. The write channel

performs processing, such as encode processing, on

5   the write data transferred from a host system 300 or

another disk drive 200 and sends a result to the write

amplifier. The write head writes the data onto the

disk medium 1 in accordance with a write current which

is outputted from the write amplifier.

10   The CPU 10 serves as a main control device in the

drive 100 and has the function to control a normal

read/write operation and copying operation relating to

the present embodiment. The CPU 10 gains access to

various kinds of register groups in the HDC 9 and

15   performs a normal read/write command and has the

function to issue a write command necessary to the

copying operation relating to the present embodiment.

Further, the present drive 100 serves as

a copying source drive and has a switch 12 for

20   instructing a copying operation by the user. That is,

the switch 12 corresponds to an input unit for

inputting information (flag information) for

instructing the copying operation. The switch 12

is provided, as shown in FIG. 5 for example, on a

25   side portion or a back portion of a drive housing.

The switch 12 is so provided as to retract inside the

housing and protected from being readily contacted

from an outside.

As shown in FIG. 2, the HDC 9 of the present drive 100 has a copying command register 91 for holding information (0/1 flag information) which is input from the switch 12 to allow a copying operation to be instructed. Upon receipt of an ON operation of the switch 12 for example, the copying command register 91 sets the flag information (here, a logical 1) for instructing the copying operation.

The CPU 10 refers to the copying command register 91 and, when the flag information is set, receives a copying operation command. It is to be noted that, in accordance with the copying command transmitted from the host system 300, the HDC 9 allows the flag information to be set to the copying command register 91.

Here, the HDC 9 has a host interface 90 based on, for example, the serial ATA Interface Standard. The present drive 100 is connected to an interface unit 20 of the copying destination disk drive 200 through an interface cable 13 based on the serial ATA Interface Standard.

The copying destination drive 200 is comprised of an HDD the same type as the present drive 100 or a normal system HDD excepting the switch 12 and copying command register 91. Thus, the interface unit 20 includes, for example, a host interface based on

the serial ATA Interface Standard. The copying

destination drive 200 has a disk medium 21 the same

memory capacity and the same format as those of the

disk medium 1 of the present drive 100. Also, the

5   copying destination drive 200 includes heads necessary

to the recording or reproducing of data relative to

the disk medium 21 as well as various kinds of

constituent elements such as a read/write channel

and CPU.

10   Further, according to the present embodiment, use

can be made of a dedicated power supply unit 400

configured to supply operation power to the present

drive 100 and copying destination drive 200. That is,

the respective drives 100 and 200, being used as

15   an external memory device for the host system 300,

have their power supply received from the host system

300 and, in the case of performing an independent

copying operation, the power supply is received from

the dedicated power supply unit 400.

20   (Copying Operation)

With reference to not only FIGS. 1 and 2 but

also FIGS. 3 and 4, the copying operation will be

explained below in connection with the flowcharts of

FIGS. 3 and 4.

25   First, as shown in FIG. 6, the present drive

(copying source disk drive) 100 and copying

destination disk drive 200 are connected together

by the cable 13 based on the serial ATA Interface
Standard for example. The power supply is effected to
the respective drives 100 and 200 by means of the
dedicated power supply unit 400.

5   In the present drive 100, as shown in FIG. 3, the
CPU 10 gains access to the copying command register 91
of the HDC 9 and it determines whether or not any flag
information (corresponding to a copy command) for
instructing the copying operation is set (steps S1,

10   S2). In the present drive 100, as an initial
operation at a power ON time, the CPU 10 always gains
access to the copying command register 91 and it
determines whether the copying operation or normal
read/write operation is performed.

15   Here, in order to allow all data which is
recorded on the disk medium 1 of the present drive 100
to be coped on another copying destination drive 200,
the switch 12 is turned ON by the user. Thus, the
flag information corresponding to the copying command

20   is set to the copying command register 91 (YES in
step S2).

The CPU 10 starts not a normal read/write
operation but a copying operation for transferring all
the recording data of the disk medium 1 to the copying

25   destination disk drive 200 (step S3). The CPU 10
makes a transmit request for establishing a communica-
tion link relating to the data transfer to the copying

destination disk drive 200 via the host interface 90
(step S4).

The copying destination disk drive 200 performs
a response to the transmit request because it has the
interface unit 20 based on the same interface standard
as that of the present drive 100. Here, where the
copying destination disk drive 200 uses the interface
unit 20 of the interface standard different from that
of the present drive 100, there is no predetermined
response to the transmit request and the CPU 10
handles this as not being copiable and makes a shift
to error processing (NO in step S5). As the error
processing, error history information relating to the
copying operation is recorded, for example, on the
disk medium 1 at a system area. This error history
information can be read out from the host system 300
when the present drive 100 is connected to the host
system 300.

Upon receipt from a response from the copying
destination disk drive 200, the host interface 90 of
the present drive 100 establishes a communication link
and the data transfer is made from drive to drive (the
copying target data transfer).

The CPU 10 generates a write command via the
host interface 90 and transmits it to the copying
destination drive 200 (YES in step S5, step S6).
Here, the write command is the same as a command

associated with a normal write operation and contains
the address and transfer amount (data sector number)
of transferring record data.

Then the CPU 10 reads recorded data out of the

5   disk medium 1 through the head 2 and reproduces the
recorded data through the preamplifier circuit 7 and
read/write channel 8 (step S7).

The CPU 10 transfers the reproduced data (read
data) through the host interface 90 to the copying

10   destination disk drive 200 (step S8). The CPU 10
reads out all the data on the disk medium 1 and
repeats the copying operations until the data is
transferred to the copying destination disk drive 200
(step S9).

15   In the copying destination disk drive 200, on the
other hand, as shown in FIG. 4, upon receipt of the
transmit request from the copying source drive 100,
the interface unit 20 sends back a response to the
transmit request (step S11, S12).

20   When, after the performing of an initial
operation at a power ON time, the copying destination
disk drive 200 receives a normal read/write command,
not a transfer request, from the host system 300,
it performs a normal read/write operation.

25   The interface unit 20 receives a write command
from the copying source drive 100 and then receives
subsequently transferred data. The copying

destination drive 200 performs a write operation for
writing data on a disk medium 21 (YES in step S13,
step S14, step S15). When all the data transferred
from the copying source drive 100 is recorded on the
5   disk medium 21, the copying operation is finished
(YES in step S16).

According to the disk drive 100 of the present
embodiment, if only the switch 12 is operated to
supply power from the dedicated power supply unit 400,
10   the recorded data can be transferred from the copying
source drive 100 to the copying destination drive 200.
In the copying destination drive 200, the transferred
recording data is recorded onto the disk medium 21 by
the normal write operation. Thus, all the recorded
15   data on the copying source drive 100 can be copied to
the copying destination drive 200.

In this case, in the present embodiment, the
copying operation can be realized by independently
using the copying source drive and copying destination
20   drive 200 without the participation of the host
system.

As an application example of the present
embodiment, image data taken by a digital camera for
instance is reserved with the use of the copying
25   source drive 100. By separating the copying source
drive 100 from the digital camera (one kind of host
system 300) and independently connecting it to another

copying destination drive 200 it is possible to copy
the reserved image data to the copying destination
drive 200.

(Practical Form of Host Interface)

5   As set out above, the drive 100 of the present
embodiment is connected to the copying destination
drive 200, for example, by the cable 13 based on the
serial ATA Interface Standard and performs data
transfer. With reference to FIGS. 7A, 7B and 8,
10   an explanation will be made in more detail below about
the method for transferring data from drive to drive
based on the serial ATA Interface Standard.

        As shown in FIG. 6, the respective drives 100 and
200 are connected together by means of the cable 13
15   based on the serial ATA Interface Standard. In the
copying source drive 100, the host interface 90
prepares a write command (containing an address and
transfer sector number) in a form based on the serial
ATA Interface Standard in accordance with the flag
20   information corresponding to a copy command by the
operation of the switch 12 and transfers it to the
copying destination drive 200.

        The copying destination drive 200 receives
the write command and subsequent data through the
25   interface unit 20 based on the serial ATA Interface
Standard and writes (copies) these on the disk
medium 21.

In the serial ATA Interface Standard, as in the case of the host system 300, the disk drive 100 (or 200) on the device side can issue a request (transmit request) for a start of data transfer. In the serial

5   ATA Interface Standard, as shown in FIG. 6, respective standards of a signal interface connector connected by the cable 13 and power supply connector for the connection of the power supply cable are set.

FIGS. 7A and 7B each are views showing one

10 practical form of a transmit sequence when data transfer is effected under the serial ATA Interface Standard. FIG. 8 is a view showing an array of register groups called the FIS (Frame Information Structures) under this Standard. The host interface

15 90 of the present drive 100 transfers a write command and recorded data to the copying destination drive 200 with the use of the FIS register groups.

FIG. 7A shows a sequence of the copying source drive 100 and FIG. 7B shows a sequence of the copying

20 destination drive 200. Here, the transmit sequence under the Standard is a Primitive level sequence. "Primitive" denotes a minimal unit to be transferred and is comprised of data bit number of the Dword, noting that the Dword means 32 bits.

25 As shown in FIG. 7A, the data source drive 100 transmit X_RDY Primitive as a transmit request. As shown in FIG. 7B, the copying destination drive

200 sends back R_RDY Primitive as a response.
Upon receipt of the response (R_RDY Primitive), the
copying source drive 100 transmits a Frame (here,
Frame: a write command) corresponding to 5 Dwords

5   in the FIS register group. It is to be noted that
the transmit frame contains FIS contents with SOF
Primitive as a start and EOF Primitive as an end.

Here, the format of the write command as a
transit request is comprised of FIS register groups as

10   shown in FIG. 8. That is, a data transfer destination
address for example is set by Cyl Low register and Cyl
High register for setting a cylinder address on the
disk medium 1. Further, the sector transfer number is
set to a Sector Number register for setting a data

15   selector number. The method for setting these
register groups is applied under the serial ATA
Standard.

Then, the copying source drive 100 transmits
the recorded data subsequent to the write command at

20   a frame corresponding to 5 Dwords. Stated in more
detail, the copying source drive 100 transmits
recorded data at a sector unit, noting that, here,
a data amount corresponding to one sector corresponds
to 128 Dwords. Thus, the copying source drive 100

25   performs data transfer at 128-times transmit sequence
in the case of transmitting the recorded data of 512
bytes corresponding to one sector.

(Another embodiment)

FIG. 9 is a block diagram showing another embodiment.

The present variant shows a structure for realizing a copying operation between those disk drives connected to external interfaces 30A and 30B (under the serial ATA Interface Standard) in a host system 300 such as a PC.

As a copying source drive 100, use is made of an HDD the same as in the embodiment above and that, as the copying destination drive, use is made of the CD-RAM 500. The CD-RAM drive 500 is one kind of rewritable optical disk drive with a rewritable optical disk (compact disk) used as a recording medium.

The host system 300 has a PCI bus 31 as an internal bus 31 and, through the bus 31, a bridge 32 is connected to the external interfaces 30A, 30B. To the bridge 32, a CPU 33, main memory 34, etc., in the host system 300 are connected.

The copying source drive 100 and copying destination drive 500 are connected to the external interfaces 30A and 30B, as set out above, respectively through cables 13A and 13B. It is to be noted that an internal power supply unit 35 in the host system 300 supplies power to the copying source drive 100 and copying destination drive 500.

In this structure, simple by the operation of
a switch 12 in the copying source drive 100, all data
recorded in a disk medium of the copying source drive
100 can be transferred to the copying destination

5   drive 500 and copied to the drive 500. Even in
the present embodiment, the copying operation is
basically the same as that in the above embodiment but
a write command and data from the copying source drive
100 are transferred to the copying destination drive

10   500 through the cable 13B, external interface 30A, PCI
bus 31 and external interface 30B.

In the copying destination drive 500, the
recorded data thus transferred is recorded onto
a rewritable optical disk (recording medium) in

15   accordance with the write command based on the serial
ATA Interface Standard. Here, in the copying
destination drive 500, a memory capacity of the
optical disk (memory medium) is equal to, and greater
than, that of the copying source drive 100.

20   It is needless to say that this embodiment can be
applied to the case where the CD-RAM drive 500 serves
as a copying source drive and the HDD 100 serves as
a copying destination drive.

According to the present embodiment and another

25   embodiment, it is possible to readily realize a
copying operation from disk drive to disk drive.
That is, when a copying operation is instructed

through a switch means for example in the present disk
drive, a communication link is established to the
copying destination disk drive to allow recorded data
to be transferred as a copying target. As in the case
of a normal write operation, the copying destination
disk drive allows the recorded data which is
transferred from the present drive (copying source
disk drive) to be written onto the corresponding disk
medium. Thus, it is possible to realize the copying
function through a transfer of the recorded data from
disk drive to disk drive.

Additional advantages and modifications will
readily occur to those skilled in the art. Therefore,
the invention in its broader aspects is not limited to
the specific details and representative embodiments
shown and described herein. Accordingly, various
modifications may be made without departing from the
spirit or scope of the general inventive concept as
defined by the appended claims and their equivalents.